


# Flexible PVC Cleanout/Test Caps

## Dallas Specialty Dal-Cap™ Product Line



PART #	SIZE	FITS PIPE SIZE	CAP ID	MIN	MAX	DEPTH	BAND
DC-05 *	1/2"	1/2" Plastic, Steel / 3/4" Copper, SS	.84"ID	.80"	.882"	.5625"	DS-16
DC-34 *	3/4"IPS	3/4" Plastic, Steel / 1" Copper, SS	1.05"ID	1.00"	1.105"	.5625"	DS-16
DC-1 *	1"	1" Plastic, Steel / 1-1/4" Copper, SS	1.315"ID	1.25"	1.385"	.5625"	DS-32
DC-114 *	1-1/4"	1-1/4" Plastic, Steel / 1-1/2" Copper, SS	1.65"ID	1.55"	1.735"	.5625"	DS-32
DC-15	1-1/2"	1-1/2" Plastic, Cast Iron, Copper, Steel	1.90"ID	1.80"	2.00"	1.00"	DS-32
DC-15COP	2"CTS	1-1/2" Plastic, Cast Iron, Copper, Steel	1.625"ID	1.58"	1.70"	1.09"	DS-40
DC-2	2"IPS	2" Plastic, Cast Iron, Copper, Steel, SS	2.375"ID	2.25"	2.50"	1.09"	DS-40
DC-2COP	2"CTS	2" Plastic, Cast Iron, Copper, Steel	2.125"ID	2.02"	2.235"	1.09"	DS-40
DC-25	2-1/2"IPS	2-1/2" Plastic, Cast Iron, Copper, Steel, SS	2.875"ID	2.72"	3.015"	1.09"	DS-48
DC-3	3"IPS	3" Plastic, Cast Iron, Copper, Steel	3.50"ID	3.325"	3.675"	1.25"	DS-60
DC-3COP	3"CTS	3" Plastic, Cast Iron, Copper, Steel	3.125"ID	2.97"	3.285"	1.25"	DS-60
DC-4	4"IPS	4" Plastic, Cast Iron, Copper, Steel	4.50"ID	4.275"	4.725"	1.28"	DS-72
DC-4COP	4"CTS	4" Plastic, Cast Iron, Copper, Steel	4.125"ID	3.92"	4.335"	1.28"	DS-72
DC-5	5"IPS	5" Plastic, CI, Copper, ST/ 4" Clay, Concrete	5.62"ID	5.35"	5.90"	1.56"	DS-96
DC-6	6"IPS	6" PL, CI, Copper, ST, SS / 5" AC, Concrete	6.50"ID	6.18"	6.825"	1.50"	DS-116
DC-8	8"IPS	8" PL, CI, Copper, ST, SS	8.50"ID	8.08"	8.925"	1.50"	DS-152
DC-10	10"IPS	10" PL, CI, Copper, ST, SS / 8" Concrete	10.60"ID	10.07"	11.125"	1.50"	DS-188
DC-12	12"	12" PL, CI, ST, DI / 10" Concrete	12.60"ID	11.975"	13.20"	1.50"	DS-224
DC-15LDC	15"	15" PL, CI, ST, DI / 12" Concrete (with band)	15.875"ID	15.405"	16.10"	2.50"	DS-270
DC-18LDC	18"	18" PL, CI, ST, DI (with band)	18.00"ID	17.605"	18.25"	2.50"	DS-270

\* Not UPC Listed

### Dal-Cap™ / Material

- Manufactured in the USA
- Meets material requirements of IPC/IRC
- cUPC meets Canadian Standard
- Conforms to ASTM D-5926
- Non-Phthalate & Lead free resins

### Dal-Cap™ Features

- Maximum Flexibility to accommodate all types of pipe
- May be used above or below ground
- Can be used for testing but not for pressure
- Temporary or permanent
- Reusable

### Dallas Bands

- All Stainless Bands
- Band: 1/2" width AISI 301 SS
- Hex Head Screw: 5/16" AISI 401SS
- Housing: AISI 301 SS
- 60in/lb installation torque
- Meets SAE J1670

**Dallas Specialty** Flexible PVC Cleanout Caps can be used for above ground or underground applications

- High durometer Flexible PVC Resins allow maximum flexibility and multiple pipe size applications
- 301 Series Stainless Steel Band Max install 60in/lb torque
- Full range of sizes available from 1/2" to 18" IPS
- Reusable, Durable & Reliable
- Phthalates Free Flexible PVC Resin



**DALLAS SPECIALTY & MFG. CO.**

1161 RUGGLES ST GRAND PRAIRIE, TX 75050

972-641-8444 \* 1-800-222-5644 \* fax 972-641-8488



[www.dallasspecialty.com](http://www.dallasspecialty.com)