


SPECIFICATIONS

Dallas Specialty Flexible Pipe Coupling for Sewer & Drain applications

Part# **DS06R-1212**

FITS: 12"RCP Reinforced Concrete Pipe x 12" CI/PVC Pipe



Coupling Made to ID Specifications

Picture may not represent part # listed here as some couplings may be reducing sized couplings

A SIDE (ID)	B SIDE (ID)	C SIDE HEIGHT
16.30"	12.60"	6.50"

Max Temp	140°degree F
Min Temp	-30°degree F
Pressure	Non-Pressure
Material	Flexible PVC
Coupling Wall Thickness	1/2"wall

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Case Quantity	3 pc / case
Band Series	301SS/304SS Series SS
Clamps	Constant Tension Bands

COUPLING

- Manufactured in the USA
- Meeting Material Requirements of IPC[®] / IRC[®]
- cUPC[®] Meets Canadian Standards
- ASTM C-1173 D-5926
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI



Clamps

- Worm Gear Clamps: 2"Width AISI 301SS
- Torque: 60in-lb Install Torque
- Band Screw: 5/16"Hex Head AISI 301SS
- Band Housing: AISI 304SS
- Meets Requirements: SAE J1670

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050
P: 972-641-8444 • 800-222-5644 • F: 972-641-8488
Email: ds@dalspc.com • www.dallasspecialty.com