# **DS109**

## **DALLAS SPECIALTY** Round Valve Box w/Single Outlet

6-1/4"Diameter x 9"Deep

Case Quantity 36/case Pallet Quantity 720pc (20cases)

Mfg'd in the USA



### MODEL# DS109B ASSEMBLED WITH LID #DS109L

Body accommodates flush Snap-down Dallas Specialty LIDS

**MATERIAL: POLYPROPYLENE** 

**DIMENSIONS:** TOP 6-1/4"ID x 6-1/2"OD / BASE 7-1/2"ID x 7-3/4"OD

**OUTLETS: SINGLE OUTLET SIZED 2-1/2"** 

SPECS: ASTM

**BOX ADDITIONS/COMPATIBILITY:** Body is standard economy box body without alterations or additions. Lid's available in a variety of colors &

configurations



#### MODEL# DS109L ASSEMBLED ON #DS109B STANDARD BODY

MATERIAL: POLYPROPYLENE

LID DIMENSIONS/FLUSH FIT SNAP-DOWN: 6-1/2"OD x 1-1/2"THICKNESS

COLOR: GREEN (FOR YARDS, PLANTERS, PARKWAYS, GRASS AREAS, GOLF

COURSES, OR IRRIGATION VALVE APPLICATIONS

FIT: FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS (OVERLAPPING STYLE LID)

REMOVE LID USING 1"HOLE ON TOP OF LID

MARKINGS: STANDARD MFG MARKINGS & IDENTIFICATION

CUSTOM MARKINGS AVAILABLE & LOGOS

SPECS: ASTM

LID ADDITION OPTIONS: LIDS AVAILABLE IN GREEN, PURPLE, BLACK, TAN, BLUE AND AVAILABLE WITH A VARIETY OF MARKINGS SUCH AS WATER, RECLAIMED WATER, NO MARKINGS (BLANK) AND OTHER MARKINGS. PLEASE CONSULT WITH YOUR DALLAS SPECIALTY REPRESENTATIVE



## **PROPERTIES / TEST VALUES**

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in IZOD IUN 18C: 5.3 ft lbs/in



® DALLAS SPECIALTY & MFG. CO.

1161 RUGGLES ST GRAND PRAIRIE, TX 75050

972-641-8444 \* 1-800-222-5644 \* fax 972-641-8488

www.dallasspecialty.com