

DS1500R

DALLAS SPECIALTY RECTANGULAR JUMBO METER BOX - 22"x 15"x 12"

PALLET QTY / 32pc

MFG'D IN THE USA

BOX

MODEL# DS1500B BODY IS ASSEMBLED WITH DS1500RL BLACK PLASTIC METER READER LID TO MAKE #DS1500R - BOX ACCOMODATES FLUSH OR OVERLAPPING STYLE DS LIDS

DIMENSIONS: 12"Deep Box - Top Dimensions 21-1/4"od x 15-1/2"od
Base Dimensions 25-7/8"od x 19-3/4"od

MATERIAL: POLYPROPYLENE

OUTLETS: SINGLE PIPE OUTLET SIZED 2-3/4" - BOX IS AVAILABLE WITH DUAL OUTLETS TO ACCOMMODATE DOUBLE CHECK VAVLE INSTALLATIONS

BOX ADDITIONS: DUAL OUTLETS, EXTENSION BOX PART NUMBER #DS750EXT AVAILABLE FOR 6"RISE AND CAN ACCOMMODATE MULTIPLE EXTENSIONS FOR FURTHER RISE

LID

MODEL#DS1500RL—SOLID PLASTIC BLACK METER READER LID SNAPS-IN (FITS FLUSH) ASSEMBLED ON DS1500B BOX BODY TO MAKE DALLAS SPECIALTY JUMBO BOX #DS1500R

USAGE: FOR ASSEMBLY ON DS1500B OR DS750 BOX/BODIES

DIMENSIONS: Flush Meter Reader Lid: 19-3/4"x13-7/8"od x 1-1/2"height

MATERIAL: POLYPROPYLENE

LID COLOR: BLACK

FIT: FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS

REMOVE LID USING 1"HOLE ON TOP OF LID

MARKINGS: STANDARD MFG MARKINGS & IDENTIFICATION

LID ADDITION OPTIONS TO DS1500RL: 2"TOUCH READ HOLE BOX ACCOMODATES DS1500SCIL (SOLID CAST IRON LID FOR LIGHT SIDEWALK/DRIVEWAY TRAFFIC) AND MULTIPLE OTHER LID VARIETIES



PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in



ds® **DALLAS SPECIALTY & MFG. CO.**
1161 RUGGLES ST GRAND PRAIRIE, TX 75050
972-641-8444 * 1-800-222-5644 * fax 972-641-8488

www.dallasspecialty.com