

SPECIFICATIONS


Sewer & Drain Shielded Pipe Coupling



DS Part# **DS56-3215SR**

FITS: 3"CAST IRON/PVC PIPE x 2-1/2"CAST IRON/PVC PIPE

Accommodates Pipe OD's 3.20" - 3.55" x Pipe OD'S 2.75" - 3.05"



Coupling Made to ID Specifications



A SIDE (ID)	B SIDE (ID)	C SIDE HEIGHT
3.38"	2.875"	4.00"

Coupling is assembled with (1) Flexible PVC Bushing on 2-1/2"CI/PVC end to accommodate pipe od's 2.75" to 3.05"

Max Temp	140°degree F
Min Temp	-30°degree F
Pressure Rating	No Pressure / Max 3-4 PSI
Material	60/EPDM Rubber
Coupling Wall Thickness	1/2" Thick

Install Torque	Shield 60in-lb torque / Clamps 60in-lb torque
Meets ASTM	C1173 / D5926
Quantity	24/case
Band Series	301SS / 304SS Series Stainless Steel
Clamps/Bands	All Stainless Worm Gear Clamp 60in-lb Torque

COUPLING & Bushing(s)

- Manufactured in the USA
- Meeting Material Requirements of IPC[®] / IRC[®]
- cUPC[®] Meets Canadian Standards
- ASTM C-1173 D-5926
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI



SS Clamps/Stainless Shield

- (4) 1/2" Wide/AISI 301SS
- Installation Torque: 60in-lb
- Screw: 5/16" Hex Head /AISI 301SS
- Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670
- HD Shield: .012 Thickness with 5/16" HH - 60lbTq



Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • www.dallasspecialty.com