

# SPECIFICATIONS


# Eccentric Flexible PVC Pipe Coupling

for Sewer & Drain applications



Part# **DS56-43E**

FITS: 4"Cast Iron / PVC Pipe x 3"Cast Iron / PVC Pipe accommodates size range 4.25"-4.55" Pipe OD's x 3.25-3.50" Pipe OD's (+/-2%PipeOD)



Coupling Made to ID Specifications & assembled with Flexible PVC Bushing to accommodate eccentric size reduction



"A" (ID)	"B" (ID)	"C" WIDTH
4.38"	3.38"	4.00"


Maximum Temperature	140°degree F
Minimum Temperature	-30°degree F
Pressure Rating	No Pressure / for drainage
Material / Resins	Flexible PVC - 55-60
Coupling Wall Thickness	3/8"

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Quantity/Case	12 pc / case
Band Series	301 Series Stainless
Clamps/Bands	Worm Gear Style

## Coupling

- Meeting Material Requirements of IPC<sup>®</sup>/IRC<sup>®</sup>
- cUPC<sup>®</sup> Meets Canadian Standards
- ASTM C-1173 D-5926 
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI

## Clamps

- (2) DS-80 Clamps - 1/2"Wide/ 301SS Stainless Steel
- Installation Torque: 60in-lb
- Clamp Screw: 5/16"Hex Head /AISI 301SS
- Clamp Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670 

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, $\pm 3$ 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS  
SPECIALTY  
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • [www.dallasspecialty.com](http://www.dallasspecialty.com)