

SPECIFICATIONS

Flexible PVC Pipe Coupling

for Sewer & Drain applications




Part pictured may not be actual coupling, picture for reference only

Part# **DS70-66**

Fits : 6"ADS/Corrugated Pipe x 6"Cast Iron/PVC Pipe

Accommodates pipe size range 6.80"-7.20"pipe od's x 6.30"-6.70" Pipe OD's
Part is molded with internal ridge to securely accommodate corrugated pipe



Coupling Made to ID Specifications

"A" (ID)	"B" (ID)	"C" WIDTH
7.00"	6.50"	6.00"




Maximum Temperature	140°degree F
Minimum Temperature	-30°degree F
Pressure Rating	No Pressure / for drainage
Material / Resins	Flexible PVC
Coupling Wall Thickness	3/8" Thickness

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Case Qty	15pc/cs
Clamp SS Series	301 Series Stainless Steel
Clamps/Bands	(2) Worm Gear All Stainless Clamps

Coupling

- Meeting Material Requirements of IPC[®]/IRC[®]
- cUPC[®] Meets Canadian Standards
- ASTM C-1173 D-5926 
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI

Clamps

- (2) All SS Clamps / 1/2" Wide - 301SS Stainless Steel
- Installation Torque: 60in-lb
- Clamp Screw: 5/16" Hex Head / AISI 301SS
- Clamp Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670 

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • www.dallasspecialty.com