

DS1200BI

DALLAS SPECIALTY RECTANGULAR VALVE BOX - 17"WIDE x 12"LONG x 12"DEEP

PALLET QTY / 72pc

MFG'D IN THE USA

BOX

MODEL # DS1200B ASSEMBLED WITH DS1200IBL (BLACK LID)

BOX ACCOMODATES FLUSH OR OVERLAPPING STYLE DS LIDS

MATERIAL: POLYPROPYLENE / OUTLETS: SINGLE / 2-3/4" - PIPE SLOT

SPECS: ASTM / BOX ADDITIONS/COMPATIBILITY:DS600EXT 6"EXTENSION

BOX DIMENSIONS: TOP - 17-1/8" x 11-7/8"OD / BASE - 21" x 16-5/8"OD

BOX DEPTH: 12"



PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in

LID

MODEL# DS1200IBL ASSEMBLED ON DS1200B (SINGLE OUTLET BOX)

FOR ASSEMBLY ON DS1200B BODY / LID DIMENSIONS: 15-3/8"x 10-1/8"OD

MATERIAL: POLYPROPYLENE

COLOR: BLACK (USED IN YARDS, PLANTERS, PARKWAYS, GRASSY AREAS, GOLF COURSES, AND/OR VALVE & IRRIGATION CONTROLS APPLICATIONS)

FIT: FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS

LID REMOVAL: USING 1"HOLE ON TOP OF LID

MARKINGS: STANDARD MFG MARKINGS & IDENTIFICATION CUSTOM MARKINGS AVAILABLE & LOGOS

SPECS: ASTM

LID ADDITION OPTIONS: 2"TOUCH READ HOLE, AND/OR AMR ATTACHMENT, AND/OR SOCKET BOLT LOCK



ds® **DALLAS SPECIALTY & MFG. CO.**
1161 RUGGLES ST GRAND PRAIRIE, TX 75050
972-641-8444 * 1-800-222-5644 * fax 972-641-8488

www.dallasspecialty.com