

# DS1500IB

**DALLAS SPECIALTY** RECTANGULAR JUMBO VALVE BOX - 21" WIDE x 15" LONG x 12" DEEP  
PALLET QTY / 32pc

MFG'D IN THE USA

## BOX

**MODEL#** DS1500B BODY IS ASSEMBLED WITH DS1500IBL BLACK PLASTIC SOLID IRRIGATION LID TO MAKE #DS1500IB

**DIMENSIONS:** 12" Deep Box - Top Dimensions 21-1/4" od x 15-1/2" od  
Base Dimensions 25-7/8" od x 19-3/4" od

**MATERIAL:** POLYPROPYLENE

**OUTLETS:** SINGLE PIPE OUTLET SIZED 2-3/4" - BOX IS AVAILABLE WITH DUAL OUTLETS TO ACCOMMODATE DOUBLE CHECK VALVE INSTALLATIONS

**BOX ADDITIONS:** DUAL OUTLETS, EXTENSION BOX PART NUMBER #DS750EXT AVAILABLE FOR 6" RISE AND CAN ACCOMMODATE MULTIPLE EXTENSIONS FOR FURTHER RISE

## LID

**MODEL#** DS1500IBL—SOLID PLASTIC BLACK IRRIGATION LID SNAPS-IN (FITS FLUSH) ASSEMBLED ON DS1500B BOX BODY TO MAKE DALLAS SPECIALTY JUMBO BOX #DS1500IB PART NUMBER

**USAGE:** FOR ASSEMBLY ON DS1500B OR DS750 BOX/BODIES

**DIMENSIONS:** Flush Irrigation Lid: 19-3/4" x 13-7/8" od x 1-1/2" height

**MATERIAL:** POLYPROPYLENE

**LID COLOR:** BLACK

**FIT:** FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS

REMOVE LID USING 1" HOLE ON TOP OF LID

**MARKINGS:** "WATER METER" & STANDARD MFG MARKINGS AND IDENTIFICATION

**LID ADDITION OPTIONS TO DS1500IBL:** 2" TOUCH READ HOLE AVAILABLE. BOX ALSO ACCOMMODATES DS1500SCIL (SOLID CAST IRON LID FOR LIGHT SIDEWALK/DRIVEWAY TRAFFIC) AND MULTIPLE OTHER LID VARIETIES



## PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in



**ds**® **DALLAS SPECIALTY & MFG. CO.**  
1161 RUGGLES ST GRAND PRAIRIE, TX 75050  
972-641-8444 \* 1-800-222-5644 \* fax 972-641-8488  
[www.dallasspecialty.com](http://www.dallasspecialty.com)